

CISCO CATALYST 1300 SERIES

Cisco C1300-24T-4X Managed Switch

High-performance 24-port Gigabit managed switch featuring 4 fixed 10-Gigabit SFP+ uplinks, 128Gbps switching capacity, advanced Layer 3 static routing, and robust enterprise security for modern business networks.

[Request Pricing](#)[WhatsApp](#)

NexoGet



nexoget.com

Ports

Uplinks

24x Gigabit RJ-45

4x 10G SFP+

Switching Capacity

128 Gbps

Routing

Layer 3 Static

PRODUCT OVERVIEW

Cisco C1300-24T-4X Switch

The Cisco C1300-24T-4X is part of the Cisco Catalyst 1300 Series, delivering reliable, secure, and cost-effective managed switching for growing business environments. It combines 24 ports of Gigabit Ethernet connectivity with 4 dedicated 10-Gigabit SFP+ uplink slots, allowing businesses to eliminate network bottlenecks and connect seamlessly to high-speed core switches and servers.

Designed for ease of deployment and powerful management, the switch supports intuitive web-based configuration alongside traditional command-line interfaces (CLI). Built-in security safeguards ensure your corporate network infrastructure remains protected against unauthorized access.

KEY FEATURES

Engineered for Enterprise Performance

24G

Gigabit Connectivity

24 high-speed 10/100/1000 copper ports for robust end-device and workstation connectivity.

10G

10G SFP+ Uplinks

Four dedicated 10-Gigabit SFP+ transceiver slots to deliver high-bandwidth core aggregation.

L3

Layer 3 Routing

Supports static routing and Inter-VLAN routing to segment traffic efficiently across subnets.

SEC

Advanced Security

Includes IEEE 802.1X, Access Control Lists (ACLs), DHCP snooping, and port security safeguards.

WEB

Intuitive Management

Manage via modern embedded web UI, CLI, SNMP, or Cisco Business Dashboard.

Rack-Mount Design

Compact 1U rack-mountable form factor built for professional server room deployments.

TECHNICAL SPECIFICATIONS

Cisco C1300-24T-4X Specifications

Specification	Details
Brand	Cisco
Model	C1300-24T-4X
Series	Cisco Catalyst 1300 Series
Device Type	Managed Layer 3 Switch
Interfaces	24 × 10/100/1000 Gigabit Ethernet ports
Uplink Ports	4 × 10G SFP+ fixed slots
Switching Capacity	128 Gbps
Forwarding Rate	95.23 Mpps (64-byte packets)
MAC Address Table	Up to 16,000 entries
Jumbo Frames	Up to 9000 bytes
Routing Capabilities	Static routing, Inter-VLAN routing, RIP

Specification	Details
Security	802.1X, ACLs, DHCP Snooping, Dynamic ARP Inspection
Management	Web UI, CLI, SNMP v1/v2c/v3, Cisco Business Dashboard
Power Supply	Internal Power Supply (100–240V AC)
Form Factor	1U Rack-Mountable
Dimensions (W x D x H)	445 × 240 × 44 mm (17.5 × 9.45 × 1.73 inches)
Net Weight	~3.14 kg (6.92 lbs)

Ordering Note: Please confirm your precise hardware configuration, required transceivers, power cords, and shipping destination with NexoGet prior to placing your order.



Need Pricing or Availability for C1300-24T-4X?

Contact NexoGet for competitive pricing, stock availability, certified Cisco hardware condition, accessories, and global shipping quotations.

 **+971 56 825 8489**

 **info@nexoget.com**



Chat with NexoGet on WhatsApp

Visit NexoGet.com →