

— CISCO BUSINESS 1300 SERIES

Cisco C1300-12XS

Managed Switch

The Cisco C1300-12XS is an advanced layer 3 managed switch featuring 12 high-density 10G SFP+ fiber ports, designed for enterprise core and distribution layers requiring robust throughput, high-speed aggregation, and comprehensive security.

[View Full Specifications](#)[WhatsApp NexoGet](#)

NexoGet



nexoget.com

12x

10G SFP+ Fiber Ports

L3

Static Routing Support

1RU

Rack-Mountable Form Factor

Web/CLI

Intuitive Management

PRODUCT OVERVIEW

High-Performance Core & Distribution Switching

Engineered for growing business networks, the Cisco C1300-12XS delivers uncompromised fiber connectivity, advanced security features, and reliable management capabilities to support modern enterprise infrastructures.

10G**High-Density Fiber**

Equipped with 12 high-speed 10G SFP+ slots optimized for robust core aggregation and long-distance connectivity.

L3**Advanced Routing**

Supports advanced Layer 2 switching alongside robust Layer 3 static routing for efficient traffic segmentation.

SEC**Enterprise Security**

Includes 802.1X port authentication, Access Control Lists (ACLs), and secure management protocols.

UI**Flexible Management**

Manage effortlessly via intuitive Web UI, standard Command Line Interface (CLI), or SNMP.

1RU**SYN**

Rack Optimized

Compact 1U rack-mountable design engineered for efficient data center space utilization and thermal performance.

Cisco Integration

Seamlessly integrates with Cisco Business Dashboard and standard corporate networking architectures.

01 / TECHNICAL SPECIFICATIONS

Cisco C1300-12XS Detailed Specifications

Technical parameters and hardware attributes for system integration and network design.

Manufacturer	Cisco Systems, Inc.
Product Family	Cisco Business 1300 Series (CBS1300)
Model	C1300-12XS
Device Type	Managed Switch - Layer 3 / Layer 2
Form Factor	Rack Mountable (1RU optimized design)
Total Interfaces	12 x 10G SFP+ fiber slots
Console Port	RJ-45 / USB Type-C console port
Switching Capacity	240 Gbps
Forwarding Rate	178.56 Mpps (64-byte packets)
Memory & Flash	512 MB DRAM / 256 MB Flash
Management Protocols	Web UI, CLI, SNMP v1/v2c/v3, Cisco Business Dashboard

Security Features	802.1X, Access Control Lists (ACLs), Port Security, Secure Shell (SSH)
Power Supply	Internal redundant-ready power supply (AC 100-240V)
Operating Temperature	0 to 50 °C (32 to 122 °F)

02 / PACKAGING & SHIPPING

Dimensions, Weight and Shipping Information

Physical measurements of the hardware unit and estimated retail packaging details.

Device Dimensions	Approx. 445 × 240 × 44 mm (Standard 1U)
Net Weight	Approx. 2.65 kg
Package Dimensions	Approx. 550 × 350 × 120 mm (Retail box)
Gross Weight (with Box)	Approx. 3.80 – 4.10 kg (including accessories & rackmount kit)

03 / PROCUREMENT

Commercial Order & Inquiry

Verify stock availability, warranty terms, and international shipping options with our sales team.

Note: Ensure compatibility with your network transceivers and core topology before finalizing your purchase order.



Need a quote for Cisco C1300-12XS?

Contact NexoGet for pricing, stock availability, bulk inquiries, and international shipping details.

+971 50 516 6272

info@nexoget.com

WhatsApp NexoGet

NexoGet.com