

NexoGet

CISCO CATALYST 1300

48-PORT GIGABIT

4 × 10G SFP+

MANAGED SWITCH

— CISCO CATALYST 1300 SERIES

Cisco C1300-48T-4X

48-Port Gigabit Managed Switch

The Cisco Catalyst C1300-48T-4X is a managed business switch with 48 Gigabit Ethernet access ports and four 10 Gigabit SFP+ uplinks. It is designed for enterprise, SMB, campus, branch and professional network deployments requiring high-density wired connectivity and high-speed uplinks.

[View Full Specifications](#)

[WhatsApp NexoGet](#)

NexoGet



nexoget.com

48

10/100/1000 Gigabit Ethernet Ports

4 × 10G

SFP+ Uplink Ports

176 Gbps

Switching Capacity

4.35 kg

Unit Weight

PRODUCT OVERVIEW

High-Density Gigabit Access with 10G Uplinks

The C1300-48T-4X combines 48 copper Gigabit ports with four 10G SFP+ uplinks for business networks that need scalable access connectivity. Its managed design is suitable for offices, campuses, retail, education, hospitality, branches and other professional environments.

48G**48 Gigabit Ports**

Forty-eight 10/100/1000BASE-T ports provide high-density wired connectivity for users, endpoints, servers and network devices.

10G**Four 10G SFP+ Uplinks**

Four 10 Gigabit SFP+ interfaces provide high-speed uplink connectivity for compatible optics, DACs or AOCs.

L2/3**Managed Networking**

Designed as a managed Catalyst 1300 switch for professional network control, segmentation and administration.

STK**Stacking Support**

Supported C1300 configurations can be stacked to simplify management and increase network scalability.

RACK**1U**

Rack-Mountable Design

The compact rack-mountable chassis fits standard network cabinets and equipment rooms.

Business Network Access

A practical high-density access platform for enterprise and growing business networks.

01 / TECHNICAL SPECIFICATIONS

Cisco C1300-48T-4X Detailed Specifications

The core specifications below are based on Cisco product documentation. Shipping carton measurements are retailer/shipping data and should be verified against the actual shipment.

Specification	Details
Manufacturer	Cisco Systems, Inc.
Product Family	Cisco Catalyst 1300 Series
Product Model	C1300-48T-4X
Product Type	Managed Ethernet Switch
Network Layer	Managed Layer 2 / Layer 3 switch
Ethernet Ports	48 × 10/100/1000BASE-T Gigabit Ethernet
Uplink Ports	4 × 10 Gigabit SFP+
PoE	No — non-PoE model
Switching Capacity	176 Gbps
Forwarding Rate	130.94 Mpps

Specification	Details
Packet Buffer	1.5 MB
CPU	Dual-core ARM, up to 1.4 GHz
System Memory	1 GB DDR4
Flash Memory	512 MB
Jumbo Frames	Up to 9000 bytes
Management Port	1 × RJ-45 Gigabit management port
Console	RJ-45 and USB Type-C console connectivity
Stacking	Supported; up to 8 switches on supported C1300 configurations
Power Supply	Internal universal power supply
Input Voltage	100–240 VAC, 50–60 Hz
Operating Temperature	-5°C to 50°C (23°F to 122°F)
Storage Temperature	-25°C to 70°C
Rack Mount	Yes
Certifications	UL, CSA, CE, FCC Part 15 Class A

Specification	Details
Dimensions (W × D × H)	444.3 × 288 × 43.94 mm (17.49 × 11.33 × 1.73 in)
Unit Weight	4.35 kg (9.59 lb)

Shipping information: A commonly listed retail package is approximately 59.7 × 41.7 × 9.7 cm with package weight around 5.45 kg. These values are retailer/shipping measurements, not Cisco manufacturer carton specifications.

02 / DEPLOYMENT

Where the C1300-48T-4X Fits Best

OFF

Enterprise Offices

High-density wired access for workstations, printers, endpoints and business devices.

EDU

Education and Campus

48 Gigabit access ports paired with 10G uplinks for professional campus networks.

RET

Retail and Branches

Centralized wired connectivity for stores, branches and distributed business locations.

SRV

Servers and Appliances

Gigabit access and high-speed uplinks for compatible servers and network appliances.

10G

Aggregation Uplinks

RACK

Network Cabinets

Use the four SFP+ interfaces for high-bandwidth connections toward aggregation or core equipment.

Rack-mountable chassis designed for structured network equipment installations.

03 / IMPORTANT INFORMATION

Before You Order

Model: Confirm the exact C1300-48T-4X SKU before ordering.

PoE: This model is non-PoE. For powered endpoints, choose an appropriate PoE model from the Catalyst 1300 family.

Uplinks: Four 10G SFP+ interfaces are provided; compatible optics, DACs or AOCs should match the intended network design.

Condition: Confirm stock condition, hardware revision, included accessories and delivery details with NexoGet.



Need Pricing or Availability for C1300-48T-4X?

Contact NexoGet for pricing, stock availability, product condition, compatible accessories, shipping options and enterprise IT hardware quotations.

 [+971 50 516 6272](tel:+971505166272)

 info@nexoget.com



[Chat with NexoGet on WhatsApp](#)

