

CISCO CATALYST 9300L SERIES

Cisco C9300L-48PF-4X

Network Switch

Enterprise-class managed access switch featuring 48 Gigabit Ethernet PoE+ ports, four fixed 10G/1G SFP+ uplinks and Cisco StackWise-320 technology. Designed for business, campus and enterprise network infrastructure.

[Request Pricing](#)[WhatsApp](#)

NexoGet



nexoget.com

Access Ports

PoE

48 x Gigabit

PoE+

Uplinks

4 x 10G SFP+

Stacking

StackWise-320

PRODUCT OVERVIEW

Cisco C9300L-48PF-4X Catalyst Switch

The Cisco Catalyst C9300L-48PF-4X is a managed enterprise access switch in the Catalyst 9300L family. It provides 48 Gigabit Ethernet PoE+ access ports and four fixed 10G/1G SFP+ uplinks for connecting access-layer devices to the wider network.

With support for Cisco StackWise-320, the platform can be deployed in supported switch stacks to simplify management and build scalable campus and business networks. Confirm software, licensing and feature requirements for your specific deployment before purchasing.

KEY FEATURES

Enterprise Connectivity and PoE+ Access

48

48 Gigabit Ethernet Ports

Provides 48 10/100/1000 Mbps access ports for compatible network devices.

PoE+

Power over Ethernet Plus

Supports IEEE 802.3at PoE+ for compatible access points, phones and other powered devices.

10G

Four SFP+ Uplinks

Four fixed 10G/1G SFP+ uplink ports support high-speed network connectivity with compatible optics.

320

StackWise-320

Supports Cisco StackWise-320 stacking technology for supported multi-switch deployments.

L3

Managed Switching

Designed for enterprise access networks requiring centralized configuration and network management.

1U

Rack-Mount Design

Rack-mountable 1U form factor suited to network cabinets and equipment racks.

TECHNICAL SPECIFICATIONS

Cisco C9300L-48PF-4X Specifications

Specification	Details
Brand	Cisco
Model	C9300L-48PF-4X
Product Family	Cisco Catalyst 9300L Series
Product Type	Managed Enterprise Switch
Switching Layer	Layer 2 / Layer 3 capabilities; confirm exact features against software and license
Access Ports	48 x 10/100/1000 Gigabit Ethernet
PoE Standard	PoE+ / IEEE 802.3at
PoE Budget	Up to 890W with the applicable 1100W AC power supply configuration
Uplink Ports	4 x fixed 10G/1G SFP+
Stacking Technology	Cisco StackWise-320
Stacking Bandwidth	320 Gbps

Specification	Details
Rack Form Factor	1U
Mounting	Rack mount
Power Supply	1100W AC configuration; verify installed PSU before ordering
Dimensions (H x W x D)	Approx. 4.4 x 44.5 x 48.8 cm; verify against the exact hardware configuration
Weight	Approx. 7.03 kg; configuration-dependent
Operating System	Cisco IOS XE
Deployment	Enterprise, campus and business networks

Ordering Note: Confirm the exact PID, hardware revision, power supply, PoE budget, software licensing, supported optics, stacking accessories and product condition before ordering. Switching performance and supported features may depend on the precise hardware and software configuration.

DEPLOYMENT APPLICATIONS

Where Can the Catalyst 9300L Be Used?

Enterprise Networks

Suitable for managed access connectivity in business offices and enterprise environments.

Campus Networks

Designed for campus access deployments connecting users and compatible network endpoints.

PoE Device Connectivity

Can power supported PoE+ devices such as wireless access points and IP phones within the available power budget.



Need Pricing or Availability for C9300L-48PF-4X?

Contact NexoGet for pricing, stock availability, product condition, power supply details, accessories, shipping options and enterprise IT hardware quotations.

 **+971 50 516 6272**

 **info@nexoget.com**

 **Chat with NexoGet on WhatsApp**

Visit NexoGet.com →