

— CISCO CATALYST 9300L SERIES

Cisco C9300L-48UXG-4X Managed Switch

High-performance enterprise access switch featuring 48 multi-gigabit ports (UPOE/PoE+), 4 x 10G SFP+ uplinks, Stacking capability up to 320 Gbps, Network Essentials/Advantage, and advanced enterprise-grade security and resiliency for modern networks.

✉ Request Pricing

💬 WhatsApp

NexoGet



nexoget.com

Total Ports

48 Multi-Gigabit

Uplinks

4 x 10G SFP+

PoE Power

UPOE / PoE+

Stacking Bandwidth

Up to 320 Gbps

PRODUCT OVERVIEW

Cisco Catalyst C9300L-48UXG-4X Switch

The Cisco Catalyst C9300L-48UXG-4X is part of the industry-leading Catalyst 9300 Series switching platform, built for security, IoT, mobility, and cloud. It offers flexible multi-gigabit connectivity to support high-speed Wi-Fi 6/6E access points and modern endpoint devices with robust UPOE power delivery.

Designed for enterprise campus and branch deployments, it provides high-density stacking, resilient power options, and advanced network monitoring features to ensure continuous, high-speed operations.

KEY FEATURES

Engineered for Enterprise Performance

MG

Multi-Gigabit Ports

Flexible multi-rate ports supporting 100M, 1G, 2.5G, 5G, and 10Gbps speeds over standard cabling.

10G

10G Uplinks

Equipped with fixed 4 x 10G SFP+ uplink interfaces for high-speed core aggregation.

PoE

UPOE / PoE+ Power

Advanced Power over Ethernet capabilities to power high-draw access points and IP cameras.

Stk

StackWise-320

High-density stacking architecture supporting up to 320 Gbps of stacking bandwidth.

Sec

Enterprise Security

Encrypted Traffic Analytics (ETA), AES-256 MACsec encryption, and segmentation features.

Res

High Availability

Resilient dual redundant field-replaceable power supplies and fan modules.

TECHNICAL SPECIFICATIONS

Cisco C9300L-48UXG-4X Specifications

Specification	Details
Brand	Cisco
Model	C9300L-48UXG-4X
Product Family	Cisco Catalyst 9300L Series
Total Downlink Ports	48x Multi-Gigabit (supports 100M/1G/2.5G/5G/10G)
Uplink Configuration	4 x 10G Fixed SFP+
Default Power Supply	1100W AC (Field-replaceable options available)
Stacking Bandwidth	Up to 320 Gbps (StackWise-320)
Forwarding Rate	190.48 Mpps
Switching Capacity	256 Gbps (up to 576 Gbps with stacking)
Chassis Dimensions	4.4 × 44.5 × 40.9 cm (Without PSU: 1.73 × 17.5 × 16.1 in)
Dimensions with PSU	4.4 × 44.5 × 48.8 cm (With 1100W AC PSU: 1.73 × 17.5 × 19.2 in)

Specification	Details
Net Weight (Chassis)	~7.65 kg (16.86 lbs)
Shipping Dimensions (Box)	~56 × 55 × 15 cm (22.0 × 21.6 × 5.9 in)
Gross Shipping Weight	~9.5 kg - 10.0 kg (With box and standard accessories)

Shipping & Ordering Note: Please confirm the exact power supply modules, rack-mount kits, regional power cords, and network licensing tier (Network Essentials or Advantage) before placing your order.



Need Pricing or Availability for C9300L-48UXG-4X?

Contact NexoGet for pricing, stock availability, product condition, accessories, shipping options and enterprise IT hardware quotations.

 **+971 50 516 6272**

 **info@nexoget.com**

 **Chat with NexoGet on WhatsApp**

Visit NexoGet.com →